



# Temperature Sensor for Build-In System G3/8" FLEXadapt

## Application / Specified Usage

- Temperature measuring in pipes and vessels without opening the process with prefabricated thermowells and build-in systems
- Demounting the sensor without opening the process and without electrical disconnection > avoiding downtime of the equipment at calibration and maintenance!
- Suitable at small pipe diameters with build-in system ESF-G (available for pipes DN25...DN100)

## Application Examples

- Flexible applicable for nearly every temperature measuring task in pipes and vessels
- Safe temperature measuring in hotsteam- and pressure pipes (enclosed process)
- Monitoring of CIP- / SIP-cleaning

## Hygienic Design / Process Connection

- Hygienic and easy sterilizable installation by using Negele build-in system ESF
- CIP-/ SIP-cleaning up to 140 °C
- Product contacting materials are compliant to FDA
- Sensor completely made of stainless steel

## Features

- Short reaction time, very compact measure point
- Integrated transmitter (optional)
- Threaded thermowells ESF-G1/2" for CLEANadapt can be combined with many other standard adapters. Therefore they are suitable for each application and process connection (e.g. Tri-Clamp, dairy flange (DIN 11851), DRD, Varivent, APV, BioControl...)
- Quick and easy to install with an orbital welding machine (ESF-G)
- Temperature sensors and build-in systems with pre-defined, concerted standard lengths, reducing the variety and economize costs for storage and simplify the maintenance.
- Different types of electrical connection available
- Protection class IP 69 K (with electrical connection M12 plug)

## Options / Accessories

- 2 x Pt100 (not retrofittable)
- 2 x Pt100 with two transmitters (not retrofittable)
- Programmable transmitters MPU-4 and MPU-M with output 4...20 mA, 2-wire
- Integrated transmitters for Profibus PA and HART-protocol  
Programming adapter MPU-P 9701
- Integrated transmitter MPU-LCD with display in connecting head
- Pt100-chip with other classes of accuracy, (1/3 B, 1/10 B)
- Pre-assembled connecting cable for M12 plug
- Fixed cable in other lengths and material available

## Authorisations



## Temperatur sensor TFP-59



## Build-in system ESF ESF-G1/2", ESF-EH, ESF-KM



Temperature Sensor		
Process connection	thermowell	G3/8" external thread
Insertion length	standard	37, 83, 97, 160 mm
Materials	connection head protection tube cap nut spacer	stainless steel 1.4305 (303) stainless steel 1.4404 stainless steel 1.4571 stainless steel 1.4301, Ø 10 mm
Temperature ranges	ambient sensor tip	-50...+80 °C -50...+250 °C
Sensing resistor	acc. to DIN EN 60751	Pt100
Electrical connection	TFP-59 or TFP-179 TFP-199	cable gland M16 x 1,5 M12 plug 1.4305, 4-pin M12 plug 1.4305 fixed cable (PVC), standard: 2,5 m
Protection class		IP 69 K (with electrical connection M12 plug)

Transmitter MPU-4, MPU-10, MPU-H, MPU-M		
Temperature ranges	ambient storage	-40...+85 °C -55...+90 °C
Measuring ranges	MPU-4, MPU-H, MPU-M  MPU-10	standard: -10...40 °C, 0...50 / 100 / 150 / 200 °C special ranges free programmable standard -200...850 °C configuration occurs with Profibus
Accuracy	input	< ±0,25 °C
Temperature drift	zero, span	< 0,01 % / K
Supply	MPU-M, MPU-4 MPU-10 accuracy	8...35 V DC 9...32 V DC 0,01 % / V (reference: 12 V DC)
Output	signal accuracy burden	analog 4...20 mA (not for MPU-10) < ±0,1 % of measurement range < 600 Ω (at U <sub>B</sub> = 24 V)
Humidity	without condensation	0...98 %

Accuracy classes of temperature sensors   Tolerances for Pt100 acc. to DIN EN 60751			
Pt100	A	1/3 B	1/10 B
0 °C / 100 Ω	±0,15 K / ±0,06 Ω	±0,10 K / ±0,04 Ω	±0,03 K / ±0,01 Ω
100 °C / 138,5 Ω	±0,35 K / ±0,13 Ω	±0,27 K / ±0,10 Ω	±0,08 K / ±0,03 Ω

Table Reaction Time	ESF-G-DIN2-25	ESF-G1/2"-40	ESF-EH-125	ESF-KM-125
Medium temperature 90 °C				
t <sub>50</sub>	5,8 s	7,8 s	8,0 s	8,0 s
t <sub>90</sub>	19,0 s	21,1 s	24,0 s	24,0 s


#### Reaction Time




We recommend the use of heat-conductive paste to reduce the mentioned reaction times down to approx. 50 %!

Electrical connection without transmitter

With 1 x M12 plug




Configuration 1st M12 plug



Electrical connection with transmitter


With M12 plug




Configuration M12 plug

- 1: + supply
- 2: - supply 4...20 mA
- 3: not connected
- 4: not connected


With 2 x M12 plug




Configuration 2nd M12 plug




With cable gland



With cable gland




Configuration strip terminal



- clamps for 1st Pt100
- clamps for 2nd Pt100 (at version 2 x Pt100)

Electrical connection with two transmitter (TFP-68)

With 1 x M12-plug (sensor 1 + sensor 2)




Configuration M12-plug

- 1: + supply (sensor 1)
- 2: - supply 4...20 mA (sensor 1)
- 3: - supply 4...20 mA (sensor 2)
- 4: + supply (sensor 2)


With fixed cable PVC (0...90 °C)



Fixed cable connection with 1 x Pt100




With 2 x M12-plug (sensor 1)



Configuration M12-plug

- 1: + supply (sensor 1)
- 2: - supply 4...20 mA (sensor 1)
- 3: not connected
- 4: not connected


With 2 x M12-plug (sensor 2)




Configuration M12-plug

- 1: + supply (sensor 2)
- 2: - supply 4...20 mA (sensor 2)
- 3: not connected
- 4: not connected


TFP-59 | TFP-59.2




Drawing higher connection head for TFP-68




TFP-179 / ...



TFP-179 / ... / MPU-M



TFP-199 / ...



**Transport / Storage**

- No outdoor storage
- Dry and dust free
- Not exposed to corrosive media
- Protected against solar radiation
- Avoiding mechanical shock and vibration
- Storage temperature -55...+90 °C
- Relative humidity max. 98 %

**Conventional Usage**

- Not suitable for applications in explosive areas.
- Not suitable for applications in security-relevant equipments (SIL).

**Reshipment**

- Sensors shall be clean and must not be contaminated with dangerous media!
- Use suitable transport packaging only to avoid damage of the equipment!

**Advice to EMC**

- The device agrees to following standards: EMC directive 2004/108/EC.
- You have to guarantee the EMC directives for the entire equipement.

**Cleaning / Maintenance**

- In case of using pressure washers, don't point nozzle directly to electrical connections!

**Mechanical Connection / Installation**

- To guarantee a definite function use the Negele **FLEXadapt-system ESF!**

**Disposal**

- This instrument is not subject to the WEEE directive 2002/96/EC and the respective national laws.
- Pass the instrument directly on to a specialised recycling company and do not use the municipal collecting points.

# Temperature Transmitter MPU-LCD with Display

## Application / Specified Usage

- 4...20mA transmitter with LCD for Pt100 temperature sensor
- For installation in temperature sensor
- Sensor monitoring

## Features

- 4-digit display with green backlight
- Temperature measurement in °C and °F
- Easy range select by one button
- Lower costs for wiring because of 2-wire technology

## Note



See product information „MPU-LCD“ for details.

## Option MPU-LCD (display in the connection head)



## Accessories

**PVC-cable with M12-connection made of 1.4305, IP 69 K, unshielded**  
**M12-PVC / 4-5 m** PVC-cable 4-pin, length 5 m  
**M12-PVC / 4-10 m** PVC-cable 4-pin, length 10 m  
**M12-PVC / 4-25 m** PVC-cable 4-pin, length 25 m

**PVC-cable with M12-connection, brass nickel-plated, IP 67, shielded**  
**M12-PVC / 4G-5 m** PVC-cable 4-pin, length 5 m  
**M12-PVC / 4G-10 m** PVC-cable 4-pin, length 10 m  
**M12-PVC / 4G-25 m** PVC-cable 4-pin, length 25 m

**Programming adapter  
MPU-P 9701**

Programming adapter for  
MPU-4, MPU-H and MPU-M

## PVC-cable with M12-connection



## Programming adapter MPU-P 9701



## Order code for version with 1 x Pt100

**TFP-59** (connecting head Ø 55 mm, with spring mounted gauge slide)  
**TFP-179** (connecting head Ø 18 mm, electrical connection via M12-plug)  
**TFP-199** (connecting head Ø 18 mm, electrical connection via 2,5 m PVC-cable; other lengths: see accessories; no transmitter possible)

## Sensor length EL in mm

**037** (length 37 mm)  
**083** (length 83 mm)  
**097** (length 97 mm, for threaded thermowell ESF-G1/2"-40)  
**160** (length 160 mm)

## Diameter thermowell in mm

3

## Diameter sensor tip in mm

3

## Accuracy class Pt100

**A**  
**1/3B**  
**1/10B**

## Electrical connection

(not selectable at TFP-179 and -199)

**PG** (cable gland M16x1,5)  
**M12** (M12 plug, standard with MPU-LCD)

## Transmitter

**X** (without)

## for TFP-59

**MPU-4** (programmable)  
**MPU-10** (Profibus PA)  
**MPU-H** (HART-protocol)  
**MPU-LCD** (with display)

## only for TFP-179 (not for TFP-199)

**MPU-M** (programmable)

## Measuring range MPU

(only for types with transmitter; not for MPU-LCD)

**-10...40** (range -10...40 °C)  
**0...50** (range 0...50 °C)  
**0...100** (range 0...100 °C)  
**0...150** (range 0...150 °C)  
**0...200** (range 0...200 °C)  
**xx...yy** (special range)

TFP-59 / 083 / 3 / 3 / A / M12 / MPU-4 / 0...100 °C

Order code for version with 2 x Pt100

**TFP-59.2** (connecting head Ø 55 mm, 2 x Pt100, no transmitter possible!)  
**TFP-68** (higher connecting head Ø 55 mm, 2 x Pt100, prepared for 2 x transmitter)

**Sensor Length in mm**

- 037** (length 37 mm)
- 083** (length 83 mm)
- 097** (length 97 mm, for threaded thermowell ESF-G1/2"-40)
- 160** (length 160 mm)

**Diameter thermowell in mm**

**3**

**Diameter sensor tip in mm**

**3**

**Accuracy class Pt100**

- A**
- 1/3B**
- 1/10B**

**Electrical connection (only for TFP-59.2)**

- PG** (cable gland M16x1,5)
- 2 x PG** (2 x cable gland M16x1,5)
- 2 x M12** (2 x M12-plug)

**Electrical connection (only for TFP-68)**

- M12** (M12-plug)
- 2 x M12** (2 x M12-plug)

**Continue if TFP-68 is selected!**  
**No further options for TFP-59.2!**

**1. Transmitter**

**MPU-4** (programmable)

**Measuring Range 1. MPU**

- 10...40** (measuring range -10...40 °C)
- 0...50** (measuring range 0...+50 °C)
- 0...100** (measuring range 0...+100 °C)
- 0...150** (measuring range 0...+150 °C)
- 0...200** (measuring range 0...+200 °C)
- xx...yy** (special range)

**2. Transmitter**

**MPU-4** (programmable)

**Measuring Range 2. MPU**

- 10...40** (-10...40 °C)
- 0...50** (0...+50 °C)
- 0...100** (0...+100 °C)
- 0...150** (0...+150 °C)
- 0...200** (0...+200 °C)
- xx...yy** (special)

TFP-68 / 083 / 3 / 3 / A / M12 / MPU-4 / 0...50 / MPU-4 / 0...50